

A9 Receipt Printer

The one that creates a new trend



the ideal solution for high volume retail and hospitality environments that require fast and quiet printing with few consumables. It adopts Seiko Instruments Inc. mechanism which is the best selling thermal mechanism worldwide. Also, its new ARM 9 CPU allows printing speed 220mm/sec in Max.

- High performance CPU (ARM 9, 32bit)
- Ultra fast printing speed up to 220mm/sec
- Specially designed font provides high readability (1Byte : 14 x 28dot / 2 Byte : 28 x 28dot)
- High resolution to 203dpi
- Support various interface (RS232C/ Parallel/ USB / Ethernet / USB & Serial combo)
- Easy paper loading
- Built-in buzzer
- Available extension melody or extension voice
- Windows & OPOS Drivers
- Compatible with EPSON or STAR cash drawer by Dip switch setting.

Printing Method	Direct thermal	
Printing Speed	220 mm/sec	
Dot Density (DPI)	203.2	
Dot Pitch (mm)	0.125*0.125	
Effective Printing Width	74mm, 588dots	
Printing Direction	Unidirectional with friction feed	
Character/Line	Font A	(14*28) 42 columns
	Font B	(10*20) 58 columns
Paper	Type	Thermal paper
	Width	79.5mm (±0.5mm)
	Thickness	0.07mm
	Roll diameter	83 Ømm
Reliability	TPH Life	100km
	MCBF	60,000,000 lines
Character/Set	Alphanumeric character	95
	Extended graphic	128 x 35 page
Barcode	EAN-8, EAN-13, CODE39, CODE93, CODE128, ITF, UPC-A, UPC-E, CODABAR	
Emulation	ESC/POS command compatible	
Driver	Windows / OPOS	
Interface	Serial / Parallel / USB / Ethernet / USB+Serial combo / Wi-fi	
Power	24 VDC / 2.5A	
Data Buffer	4 Kbyte	
Cutting	Life	1,000,000 cuts
	Cutting method	Partial Cut
Temperature	Operation	0 ~ 40°C
	Storage	-20 ~ 60°C
Qualification	CE, FCC, KCC	

* Specifications are subject to change without prior notice



POSBANK® Co.,Ltd.

Room 805~808 New T Castle B/D, 429-1 Gasan-Dong, Geumcheon-Gu Seoul, Korea

Tel. +82-2-2626-9118 Fax. +82-2-2626-9119 E-MAIL Sales@posbank.com

www.posbank.com

Copyright(c) POSBANK Co.,Ltd. All rights reserved.