



HT330

4" Rugged Handheld Terminal

Android 12 with GMS certified | Removable 5200mAh battery | IP67 rating & 1.5M drop



Transform your task with Unitech's HT330 — rugged handheld terminal embedded with an unrivaled 2D engine and running on the latest Android 12. The latest Android 12 platform with GMS provides an intuitive interface to manage data effectively on a 4-inch screen and has integrated all features you need from stock checking to shipping. As a reliable work companion, HT330 shows outstanding software support as well as trustworthy scanning hardware that optimizes work performance. The removable 5200mAh Lithium-ion battery carries your task for over 20 hours, allowing a full shift to go on. Reaching IP67 enterprise protection and withstanding 1.5 drop makes HT330 a perfect tool to maximize data collection, management, and traceability in nearly every practice of retail, transportation & logistics, manufacturing, and more!

Choice of Optimum Scanning

When it comes to facilitating work efficiency and minimizing errors at service, HT330 is the best choice of optimal data collection terminal for the retail and warehousing field. This high-performance handheld terminal featuring a powerful 2D engine has upgraded to Android 12 OS to empower staff with an easy-scan, simple-check convenience. The GMS certification allows staff to access a set of pre-installed apps and services meant to boost productivity.

Extending Battery Capacity for All Day

A larger battery capacity of HT330 means fewer battery replacements and longer operation time. The removable 5200mAh Lithium-ion battery supports 20 working hours, making it a suitable device for intensive scanning scenarios, like inventory checks. The 3GB RAM/32GB Flash memory storage undertake a high volume of data even after hours.

Rich and Reliable Wireless Connection

The 802.11 a/b/g/n/ac/d/e/h/i/j/k/r/v standards and faster transmission synchronize information in real-time to ensure barrier-free communication. HT330 lays a foundation of instant visibility into what's happening and being done under 2.4G+5GHz bandwidth. The Bluetooth® 5.0 improves the connectivity of related pairing devices, and the GPS function further tracks location more precisely.

Friendly Panel in Rugged housing

The one-hand terminal combines a 4-inch touchscreen with 32 keys physical keypad, providing a flexible interface to satisfy industries' requirements. Water-resistant, dust-proof, and enduring drop to 1.5 m, HT330 can handle all demanding environments.

Features

- Powerful 2D Engine supporting major 1D/2D barcodes
- Android 12 OS with GMS-certified
- Full-shift 20 hours operation time
- Removable 5200mAh Lithium-ion battery
- Friendly panel design: 4" Touchscreen / Intuitive Backlight 32 Keys Keypad
- Ergonomic and balanced weight 295g
- Clear camera recognition: Rear 13MP, Front 5MP
- Support wireless Bluetooth® 5.0
- Enterprise Ruggness: IP67 rated protection/ 1.5M drop-to-concrete
- Support 802.11 a/b/g/n/ac/d/e/h/i/j/k/r/v standards under 2.4G+5GHz frequency
- Support MDM software and utilities such as MoboLink, StageGO, SOTI, Ivanti Wavelink, etc.





System Features

| | |
|-------------------|----------------------|
| OS | Android 12 |
| GMS certified | YES |
| CPU | Octa-core 2GHz |
| Memory | 3GB RAM / 32GB Flash |
| Languages support | Multi-languages |

Display

4", WVGA 800 X 480, Backlight (450nits)
Multi-touch panel, gloves and wet hands supported

Buttons / Keypad

Numeric (32 keys); number keys, function and direction keys with backlight

Camera

Rear 13 MP with PDAF, LED flash light
5MP Front Camera

Indicator

LED, Speaker, Vibrator

Symbologies

| | |
|-------------|-------------------------------|
| 1D Barcodes | Support all major 1D barcodes |
| 2D Barcodes | Support all major 2D barcodes |

RFID

| | |
|-----|---|
| UHF | Optional |
| HF | Optional: Frequency 13.56Mhz, ISO14443A/B, ISO15693 standard, NFC, MIFARE, Felica |

Power Source

Main battery 3.85V 5200mAh Li-ION battery (removable),
Operating time : over 20 hours
(depending on the specific environment)

Regulatory Approvals

CE, FCC, NCC, CCC, SRRC, VCCI, TELEC, RoHS, BQB, N-Mark, BSMI

Communication

| | |
|------------|---|
| Bluetooth® | Bluetooth® 5 supported |
| WLAN | 802.11 a/b/g/n/ac/d/e/h/i/j/k/r/v, fast roaming, 2.4G+5GHz, hotspot |
| WWAN | 4G: FDD-LTE B1/2/3/4/5/7/8/12/17/20/28a&b/66 TDD-LTE B38/39/40/41 3G: WCDMA B1/2/4/5/8 2G: GSM B2/3/5/8 |
| GPS | GPS/AGPS, GLONASS, BeiDou, Galileo |
| Sensors | Gyroscope, G-sensor, E-Compass, Light & Proximity Sensor |

I/O Interfaces

| | |
|----------------|---|
| USB | USB 2.0 (Type-C) |
| OTG | Yes, over USB Type-C |
| POGO PIN | Pogo Pin Rear: Support Gun grip Pogo Pin Bottom: Charging via cradle Pogo Pin Rear: Support UHF Gun Grip (optional) |
| SIM Slot | Nano SIM Slot x 2 |
| Expansion Slot | MicroSD memory card up to 256GB |
| Audio | Speaker: 1W output, 90 dB at 10cm MIC: 2 MIC design |

Enclosure

| | |
|--------------------------|--------------------------|
| Dimensions (H x W x D) | 185 mm x 70 mm x 23.8 mm |
| Weight | 295g with battery |

Environmental

| | |
|-----------------------|---------------------------------|
| Operating temperature | -20°C to 60°C |
| Storage temperature | -40°C to 70°C (without battery) |
| Charging temperature | 0°C to 45°C |
| Relative Humidity | 5% ~ 95% (non-condensing) |
| Drop Specification | 1.5m / 1.8m (with boot case) |
| Sealing | IP67 |

Software

| | |
|--------------|--|
| MDM Software | SOTI, Ivanti Wavelink, 42Gears, and MoboLink |
|--------------|--|

Accessories

| | |
|------------------------|-----------------------------|
| 3.85V 5200mAh battery | Glass Screen Protector |
| USB Type C Cable | Gun Grip |
| Hand Strap | Single Slot Charging Cradle |
| Stylus with coil strap | Single Slot USB Cradle |
| Boot Case | |



Headquarters

Taipei, Taiwan
http://www.ute.com e-mail: info@hq.ute.com

unitech America

Los Angeles
http://us.ute.com e-mail: info@us.ute.com
http://can.ute.com info@can.ute.com
Mexico
http://latin.ute.com e-mail: info@latin.ute.com

unitech Asia Pacific & Middle East

Taipei
http://apac.ute.com info@apac.ute.com / info@india.ute.com
http://mideast.ute.com info@mideast.ute.com

unitech Europe

Tilburg / Netherlands
http://eu.ute.com e-mail: info@eu.ute.com

unitech Japan

Tokyo
http://jp.ute.com e-mail: info@jp.ute.com

unitech Greater China

Beijing, Shanghai, Guang Zhou, Xiamen
http://cn.ute.com info@cn.ute.com
Taipei http://tw.ute.com info@tw.ute.com

